




Yealink T4U Series of IP Phones Specification

Model	SIP-T48U	SIP-T46U	SIP - T43U
			
LCD	7" color touch screen	4.3" color LCD	3.7" graphical LCD
Resolution	800 x 480	480 x 272	360 x 160
LCD Backlight	✓	✓	✓
Line	16	16	12
Line Key	0	10	8
Memory Key	29 touch keys	27 (3 pages of 9 keys)	21 (3 pages of 7 keys)
HD Voice	HD Speaker,HD Handset	HD Speaker,HD Handset	HD Speaker,HD Handset
Wide-band Codecs	G.722, Opus	G.722, Opus	G.722,Opus
Narrow-band Codecs	G.711(A/μ), G.729A/B, G.726,G.723.1, iLBC, Opus	G.711(A/μ), G.729A/B, G.726,G.723.1, iLBC, Opus	G.711(A/μ), G.729A/B, G.726,G.723.1, iLBC, Opus
3-way Conferencing	✓	✓	✓
Ethernet Port	Dual-port Gigabit Ethernet	Dual-port Gigabit Ethernet	Dual-port Gigabit Ethernet
PoE	✓	✓	✓
Handset Port (RJ-9)	✓	✓	✓
Headset Port (RJ-9)	✓	✓	✓
USB Port (2.0 compliant)	2	2	2
USB Headset	✓	✓	✓
USB Recording	✓	✓	✓
Yealink Bluetooth Adapter BT40/BT41	✓	✓	✓
Yealink Wi-Fi Adapter WF40/WF50	✓	✓	✓
Wireless Headset Adapter	EHS40	EHS40	EHS40
Expansion Module	EXP43	EXP43	EXP43
Foot Stand	2 adjustable angles	2 adjustable angles	2 adjustable angles
Wall Mounting	✓	✓	✓
External Yealink AC Adapter (optional)	AC 100~240V input and DC 5V/2A output	AC 100~240V input and DC 5V/2A output	AC 100~240V input and DC 5V/2A output

Issued by Yealink (Xiamen) Network Technology CO., Ltd. All rights reserved. Subject to changes in technology, design and availability.

